



28 FEB 2005  
GB 2003 / 003663



INVESTOR IN PEOPLE

The Patent Office  
Concept House  
Cardiff Road  
Newport  
South Wales  
NP10 8QQ

REC'D 18 SEP 2003

WIPO PCT


**PRIORITY DOCUMENT**  
SUBMITTED OR TRANSMITTED IN  
COMPLIANCE WITH  
RULE 17.1(a) OR (b)

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.




Signed

*P. Mahoney*

Dated 10 September 2003

**BEST AVAILABLE COPY**



03SEP02 E/45113-1 D00355  
P01/7700-0.00-0220296.8

# Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

The Patent Office

Cardiff Road  
Newport  
South Wales  
NP10 8QQ

1. Your reference M071637PGB

2. Patent (The I 0220296.8 31 AUG 2002

3. Full name, address and postcode of the or of each applicant (underline all surnames)  
Paul Anthony BONE  
7 Argyle Road, Newport  
Isle of Wight  
PO30 5SB

Patents ADP number (if you know it)

If the applicant is a corporate body, give the country/state of its incorporation

976855002

4. Title of the invention CONTAINER

5. Name of your agent (if you have one) Marks & Clerk

"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)

Alpha Tower  
Suffolk Street Queensway  
Birmingham B1 1TT

Patents ADP number (if you know it)

18002

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number	Country	Priority application number (if you know it)	Date of filing (day / month / year)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application	Number of earlier application	Date of filing (day / month / year)

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if:

- a) any applicant named in part 3 is not an inventor, or
- b) there is an inventor who is not named as an applicant, or
- c) any named applicant is a corporate body.

See note (d)) No

# Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form.  
Do not count copies of the same document

Continuation sheets of this form

Description 17

Claim(s)

Abstract

Drawing(s) 8 + 8 

10. If you are also filing any of the following, state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (Patents Form 7/77)

Request for preliminary examination and search (Patents Form 9/77)

Request for substantive examination (Patents Form 10/77)

Any other documents (please specify)

11.

I/We request the grant of a patent on the basis of this application.

Signature 

Date

30 AUG 2002

12. Name and daytime telephone number of person to contact in the United Kingdom

S. G. Mosey - 0121 643 5881

## Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

## Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 08459 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.

## CONTAINER

This invention relates to a container, particularly for liquid fuel such as petrol.

Presently known petrol cans suffer from several disadvantages. One such disadvantage is that in tipping up the can to dispense petrol therefrom it becomes difficult to control the outflow of the petrol. Another disadvantage is that as the spout is removably attachable to the can body, it can become lost and additionally if the seal between the spout and the can wears as the spout is engaged and released over a period of time, there will be leakage of petrol upon pouring from the can.

An object of the invention is to provide a container in which one or more of the above-mentioned disadvantages are overcome or at least minimised.

According to a first aspect of the invention there is provided a container for storing liquid and/or dispensing liquid therefrom, in use, the container having a body with an inlet for the entry of liquid thereinto and an outlet for dispensing liquid therefrom, and a valve associated with the outlet to control the flow of liquid therethrough, the valve having a movable valve member, movement of which is controlled by an actuator operable at the exterior of the body, the body defining a sealed enclosure when the inlet is closed and said actuator is in its non-operative position.

In said non-operative position, the actuator seals with the body. Preferably the actuator seals with a housing which is itself sealing attached to the body

at an opening in a wall thereof. Desirably the housing contains biasing means to bias the actuator to its non-operative position. Conveniently the valve member seals with a valve seat at said outlet when the actuator is in its non-operative position.

According to a second aspect of the invention there is provided a container for storing liquid and/or dispensing liquid therefrom, in use, the container comprising a body with an inlet for the entry of liquid thereinto and an outlet for dispensing liquid therefrom, a dispensing spout non-removably attached to the body at said outlet, and a valve associated with said outlet to control the flow of liquid therethrough into said spout, the valve having a movable valve member, movement of which is controlled by an actuator operable at the exterior of the body.

Preferably said dispensing spout at one of its ends is screw-threadedly engaged with said body, and desirably locking means are provided between the spout and said body to lock the spout to the body when said end of the spout is fully screw-threadedly engaged with the body. Conveniently the screw-threads of the body which are complementary to the screw-threads of the spout are provided on the exterior of a boss of the body arranged around said outlet, and when the spout is fully engaged with said body, an annular sealing ring of said spout sealing engages in a complementary annular groove in an outer end surface of said boss.

According to a third aspect of the invention there is provided a container for storing liquid and/or dispensing liquid therefrom, in use, the container comprising a body with an inlet for the entry of liquid thereinto and an outlet

for dispensing liquid therefrom, a valve associated with the outlet to control the flow of liquid therethrough, the valve having a movable valve member, movement of which is controlled by an actuator operable at the exterior of the body, the actuator being movable between a non-operative position, in which it seals an opening into the body, and an operative position, in which it allows air to pass through said opening into the body.

Preferably the actuator is a push-button which is slidable into and out of said body between its non-operative and operative positions. Desirably said push-button has a first part of its exterior surface formed sealingly to engage in said opening in said non-operative position of the push-button, and a second part of its exterior surface relieved so that when its is received in said opening in the operative position of the push-button air can pass through said opening between said relieved surface and said body. The container is thus vented as liquid is dispensed. Advantageously around the opening at the exterior of the body is an outwardly projecting, open-ended surround which is itself vented to allow air to flow into said body when the push-button is in its operative position, even if a user covers said open end of the surround in operating the push-button.

The invention will now be described, by way of example, with reference to the accompanying drawings, in which:

Figures 1 to 4 are respectively a side view, a front view, a rear view and a top plan view of a container of the invention,

Figure 5 is a side perspective view of a spout of the container of Figures 1 to 4,

Figure 6 is a fragmentary cut-away view showing a detail of locking means at one end of the spout,

Figure 7 is a fragmentary view of part of the container body at an outlet therefrom, showing a detail of locking means,

Figure 8 is a schematic, part-sectional fragmentary view of how the spout is secured to the container body and how a flexible part thereof can be locked to the body in its inoperative state,

Figure 9 is a fragmentary view of a surround on an external surface of the container body in which an opening for a push-button is provided,

Figures 10 and 11 are respectively a side view and an end view of the push-button,

Figure 12 is a side view of a housing which is secured in the body at said opening,

Figure 13 is a part-sectional fragmentary view showing the push-button and the housing assembled together at said opening,

Figure 14 is a schematic, interior side view of a further embodiment of a container of the invention,

Figure 15 is a schematic side view of a collapsible spout of the container of Figure 14,

Figure 16 shows an end of the spout of Figure 14, and

Figure 17 is a cut-away side view of a cap for extending the collapsed spout.

A container of the invention, as shown complete in a first embodiment in Figures 1 to 4 and a second embodiment in Figure 14, is in the form of a petrol can referred to generally by the numeral 10 for the first embodiment and 100 for the second embodiment. It will however be appreciated that the invention relates to containers in general, not only for liquid fuel, although it is in respect of liquid fuel to which the invention has greatest applicability and in respect of which the container of the invention will be specifically described.

A petrol can according to each of the aspects of the invention disclosed herein incorporates a push-button operated valve arrangement for controlling outflow of liquid from the container. In this regard such arrangement is generally in the forms set out respectively in British Patents Nos. 2250734 and 2316858. However where the respective arrangements of those patent specifications have been adapted for use with a petrol can rather than with a watering can as previously described, details will be given herein. However the basic structure and operation of the operating link between the push-button and the valve member of the valve arrangement remains substantially unaltered and will not be described herein.



The first embodiment of the petrol can, denoted by the numeral 10, can be formed of metal or plastics material. As shown in Figures 1 to 4, the can comprises a body 11 which has a flat base 12 so that the can is stable on a flat supporting surface. Although the can may be formed in any convenient shape, it can be seen from Figures 1 to 4 that in this embodiment the can body is oval-like in top plan view, with respective opposite sides 13,14 extending outwardly and downwardly from the can top surface 15 to an outwardly waisted portion 16, from which the sides then extend inwardly and downwardly for a short distance to the base 12. This construction provides stability to the can.

As can be seen best from Figures 1 and 3, the body is provided with two through apertures 17,18 respectively to receive a user's hand to grip and manipulate the can. The aperture 17 extends through the body of the can at a lower rear part thereof, it being intended that a user inserts his or her hand through this aperture with the thumb of that hand being used to operate a push-button 19 which is disposed adjacent to and just above said aperture 17. The aperture 18 is provided to allow the user's other hand to grip the can so as to facilitate the handling thereof, particularly where the can is full or near full and thus relatively heavy. This aperture 18 is disposed generally through the upper central part of the can body.

At its front, the can body is formed with an outwardly projecting spigot or boss 20 (Figure 8) which has an external screw-thread 21, there also being formed around the exterior surface of the boss 20, at a position below the screw-thread 21, a number of spaced locking means in the form of ramp-like

projections 22, for a purpose to be hereinafter described. In its axially directed annular end surface 23, the boss 20 is formed with an annular groove 24, for a purpose again to be described hereinafter.

At opposite sides of its top surface 15, is provided a pair of opposed wings 25 defining between them a channel in which a free end part 26 of a flexible spout 27 is intended to be received in an inoperative state of the spout, with longitudinal axially extending ribs 28 on the exterior surface of the part 26 engaging in respective complementary grooves 29 in the respective inner surfaces of the wings 25 so that the part 26 can be releasably locked in place in said channel in said inoperative state to provide convenient storage for this free end of the flexible spout. As will be appreciated, said end part 26 is shown stored in Figures 1 to 4 as well as in detail in Figure 8.

The top of the can body is formed at a position adjacent the rear thereof with an upstanding spigot or boss 30 which is externally screw-threaded and which has an inlet opening therethrough to define a filling hole for introducing fuel into the can. As shown in Figures 1 to 4, this opening is intended to be closed by a cap 31 which has an internal screw-thread complementary to the external screw-thread on the boss 30 so that the cap can be screwed down tightly into sealing engagement with the body at said boss thereby to prevent outflow of fuel at said inlet opening if, for example, the can were to be inverted. It can also be seen from the drawings that the cap 31 is joined to the body by a flexible strap 32 so that this cap 31 cannot become lost. In a similar manner a cap 33 for sealing the open free end of the spout 27 is connected to the body by a flexible strap 34.

Finally in relation to the actual structure of the can body, it can be seen from Figure 13 that the rear of the can where the push-button 19 is disposed is formed with an outwardly projecting annular flange 35 which is slightly spaced from, but surrounds, the push-button 19. This flange 35 is exteriorly threaded as at 36 for the engagement therewith of complementary thread in the interior of a cap 37 which is sized so that it can sealingly engage with the flange 35 and cover the push-button when it is in its fully extended, non-operative state, i.e. as shown in Figure 1. This cap is joined to the body by a flexible strap 38, again ensuring that the cap cannot be lost or mislaid. As will be described hereinafter, the cap, when in place, prevents accidental pushing of the button in transit and also prevents accidental operation of the button if the can were to be dropped.

Figure 1 shows, in phantom, the operating link 39 between the push-button 19 and the valve member 40 (Figure 8) of the arrangement herein before referred to in relation to British Patents Nos. 2250734 and 2316858. As mentioned above, the precise structure of this link 39 is not a feature of the present invention and either of the forms disclosed in said patents respectively could be used, or alternatively the link 39 could be an adaptation of either of said earlier constructions. However it will be noted from Figure 1 that the link is substantially straight from the push-button to the valve member 40 so that as a consequence, depression of the push-button positively pushes out the valve member so that reliable operation is ensured and that there is no danger of this shorter link sagging and thus relying on the internal liquid pressure in the can to force open the valve member. As can be seen from the drawings, the push-button is disposed at one side of the longitudinal centreline, and together with this it can also be seen that the inlet opening at

the boss 30 is similarly offset relative to this centreline, but to the opposite side thereof from the push-button 19. This is to ensure that when a user inserts a conventional petrol pump nozzle into the inlet opening the end of the nozzle does not foul the link 39, since repeated fouling of this line by the pump nozzle could result in damage to the link and the possible sagging referred to above, leading to unreliable operation of the valve member by depression of the push-button. As can be seen from Figure 8, the end of the valve member is frusto-conical and engages a valve seat at the inner end of the outlet opening in the boss 20. However for clarity a clearance is shown between the valve member 40 and its seat in Figure 8, although this would not be present in practice so that the valve member would tightly seal onto its seat when the push-button is in its inoperative position.

Now considering Figures 5 to 8, it can be seen that the spout 27, which, as stated, is flexible, has its one end provided with an internally threaded socket portion 41, the screw-thread being indicated at 42 and being complementary to the screw-thread 21 on the boss 20. As can be seen from Figures 5, 6 and 8, this screw-thread does not extend to the open outer end of the socket portion 41, but terminates short thereof. Adjacent this open end, the internal surface of the portion 41 is provided therearound with a series of spaced ramp-like locking projections 43 substantially equivalent to the projections 22 on the external surface of the boss 20. These projections 22 and 43 are arranged so that on assembly of the can during manufacture the socket portion 41 is engaged on the boss 20 and screwed-up to the position shown in Figure 8. As the portion 41 is screwed onto the boss 20, the projections 43 come into contact with the projections 22 and, due to the ramp-shapes of these, the projections 43 ride over the projections 22 in the screwing-up

direction. However once the portion 41 has been fully screwed onto the boss 20, the respective raised ends of the ramp-like projections 43 are in juxtaposition with the respective corresponding raised ends of the ramp-like projections 22 on the boss 20 such that an attempt to turn the socket portion 41 in a direction such as to unscrew it from the boss 20, results in the respective raised ends of the projections 43 engaging the respective raised ends of the projections 22 such that disengagement cannot take place so that by these locking means formed by the projections 22 and 43, the spout is locked to the can body and can only be removed therefrom by force, since it is intended that once the spout is thus fitted and locked in place by the manufacturer, it should not thereafter be separated from the can body. It can also be appreciated from Figure 8 that when the socket portion 41 is fully screwed onto the boss 20, a concentric annular flange 44 projecting outwardly from the inner surface of the socket portion 41 is tightly sealingly received in the annular groove 24 further to resist any leakage between the can body and the spout at its area of attachment. Thus not only is there a tight seal between the portion 41 and the boss 20 at the screw-threads, there is also a tight seal between the flange 44 and the groove 24.

The spout, which is of clear/translucent plastics material, is flexible and can thus be twisted, as shown in Figure 8, so that its straight cylindrical end part 26 can be engaged between the wings 25, as described, with its ribs 28 being arranged to click into the complementary grooves 29 in the wings 25 on the can body. This enables the spout to be firmly and conveniently stored when not required for use. As mentioned, the permanent attachment of the spout to the can body is a safety feature in that the spout cannot be lost so that there is no temptation for a user to try to pour liquid from the can without a spout;

such action invariably resulting in spillage of the liquid dispensed. Clearly with petrol, paraffin or the like, this represents a considerable safety risk. It will also be noted that the valve member 40 is within part of the can body itself and is not disposed at the end of the spout, as is the arrangement when the valve member is used in a watering can as described in the two above-mentioned British patents. Accordingly with this present invention the valve member is protected and is arranged so as to prevent damage thereto, so that a controllable flow of petrol, or other fuel from the can, can easily be obtained by use of the push-button arrangement. It will be appreciated that instead of ribs on the spout co-operating with complementary grooves on the wings 25, the reverse arrangement could be employed, i.e. with the ribs on the internal surfaces respectively of the wings. During manufacture the push-button operating link 39 with the valve member 40 on its one end is firstly fed through the outlet opening into the interior of the can body until the leading end of the link can be engaged with a housing 45 shown in Figure 13 and the valve member 40 reaches its seat shown in Figure 8. Once the operating link 39 has been securely engaged at the housing 45 so as to be attached to the push-button 19, so that the link 39 is disposed as shown in phantom in Figure 1, the socket portion 41 is then screwed onto the boss 20 as described. In one arrangement the push-button 19 is engaged with the housing 45 by insertion into its left-hand end as viewed in Figure 13 with the free end of the link 39 shown in Figure 13 passing through the housing and being engaged in the end of the push-button 19 received in the housing 45.

Considering now Figures 9 to 13, it can be seen that the housing 45 is of generally hollow cylindrical form having an external annular collar 46 at its one end. The housing 45 is tightly sealingly received through a circular

opening 47 in the rear wall of the can body, around which opening 47 the annular flange 35 is disposed, as shown best in Figure 13. The housing 45 is preferably secured in place at said opening 47 by adhesive or other means such that its collar 46 is positioned against or just outward of the wall of the can body at which the opening 47 is disposed, so that the collar 46 is disposed within the interior space defined by the annular flange 35. The end of the housing 45 at which the collar 46 is disposed is formed with a circular opening to allow the inwards and outwards sliding of the push-button 19 relative to the fixed housing 45, whilst the opposite end of the housing 45 is formed with an inwardly directed boss 48 through which a circular bore 49 extends for reception of the free end of the operating link 39 such that, as described on assembly, the link 39 can be pushed through the bore 49 and within the housing 45 so as to engage in an opening in the inner end of the push-button 19 so as securely to attach the link to the push-button. This inner end of the button 19 has an outwardly extending boss 50 in which is disposed the above-mentioned hole for reception of the link end 39. The boss 50 and the boss 48 act as respective location points for the opposite ends of a coiled compression spring 51 received within the housing 45 as shown in Figure 13. This spring accordingly biases the push-button to its outward, non-operative position shown in Figure 13, the force on the button drawing the link 39 taut as shown in Figure 1.

The external shape of the push-button 19 is as shown in Figures 10, 11 and 13, this being generally cylindrical but varying radially along its axial length. Accordingly next to the boss 50 is a cylindrical portion 52 which has a diameter equivalent to the diameter of the opening through the collar 46, so that, when the push-button is in its Figure 13 position, this portion 52 tightly

engages and seals with said housing 45 at the collar 46. Although not shown as such in Figure 13, it could also be arranged that the internal diameter of the housing 45 is the same as the internal diameter of the opening through the collar 46, so that there is sealing not only between the part of the portion 52 within the collar, but also for the part of the portion 52 which projects into the housing 45. However whatever the arrangement, there will be provided a tight seal between the push-button 19 and the housing 45 so as to prevent leakage of liquid from the can body at the opening in the collar and also at the opening 47. The radius of the push-button 19 reduces at the left-hand side of the cylindrical portion 52, as viewed in Figure 10, and next to this reduced radius portion is a further cylindrical portion 53 which has a diameter substantially equivalent to that of the cylindrical portion 52 so that when the button is pushed into the housing 45 this portion 53, which is longer axially than the portion 52, acts to guide the button into the housing 45 and prevent misalignment, thereby ensuring pure axial sliding. However to allow venting of the petrol can when the button is moved from its non-operative state shown in Figure 13 to its operative state where the valve member is moved off its seat to allow dispensing of liquid from the can, the further portion 53 is provided with a pair of diametrically opposite longitudinal grooves 54, 55 respectively in its external surface, each groove extending along the whole length of the portion 53. Accordingly when the button is pushed in and the portion 53 seals with the housing 45, there is nevertheless defined two airflow passages at the grooves 54 and 55 respectively so that ambient air vents the can by flowing into the housing 45 and thence into the interior of the can to replace the dispensed liquid through an opening 56 in the housing 45. This opening 56 is shown in detail in Figure 12, and may conveniently be generally rectangular, but with sloping sides. The



disposition of the housing 45 in the can body would generally be such that this opening is directed downwardly so that liquid will not remain in the housing 45 when the level of liquid in the can interior falls below the level of the housing 45. In other words the housing 45 would be disposed at 90° to the orientation shown in Figure 13 in a direction to bring the opening 56 to face the bottom of the housing. Finally it can be seen that the outer end of the push-button is formed as a cylindrical portion 57 having a diameter slightly less than that of the further cylindrical portion 53, although the diameter here is not crucial in that this part never enters the housing the 45 due to the resistance of the spring 51 and its length when coiled. As shown in Figure 13, the outer end of the push-button 19 can have an opening for reception of a peg, pin 58 or equivalent as required, and this may also form part of a fixing arrangement for securing the end of the operating link 39 to the push-button 19.

From the above it is believed that various advantageous features of the can will be apparent, these being as follows. A controllable flow of petrol, other fuel, or any other liquid is readily achievable by use of the push-button arrangement. The valve member is within the structure of the can itself rather than at the end of the spout. The spout is manufactured separately, but permanently attached to the can body during assembly. The flexible spout incorporates grooves/ribs that click into and engage with corresponding ribs/grooves at the can handle for firm fitting. The spout is made of clear plastics material for identifying whether there is fuel therein. The straight or substantially straight line followed by the link from the push-button to the valve member ensures that depressing the button pushes out the valve member, for reliable operation. The push-button is off centre, so that with or

without the inlet being off centre, a user can fill the can from a petrol pump nozzle without this nozzle coming into contact with the operating link. The locking means between the can body and the spout ensures that the spout is firmly and permanently sealingly locked into place. The grooves in the exterior surface of the push-button are long enough to allow smooth depression of the button along with airflow into the can to provide venting. The button has an associated cap to cover it when not in use, thereby to prevent accidental pushing in of the button in transit and accidental spillage of petrol or other liquid contained in the can.


Finally in relation to this first embodiment, it is noted that in Figure 9 the screw-thread 36 is interrupted by slots 59 extending inwards from the free end of the flange 35. These slots ensure that even if a user were to push in the button 19 and fully cover the outer open end of the flange 35, for example by means of the user's thumb, air would still be able to flow to the grooves 54 and 55 by passing in through the slots 59.

Another feature of this embodiment is that the angle of the valve member at its seat is less than with the watering can arrangement described in the above-mentioned British patents. Here the angle may be reduced to, for example,  $45^{\circ}$  to inhibit pulling back of the valve member into the can body. This will overcome any tendency for contraction of the can, due to temperature change, to suck the valve into the interior of the can. Finally it is mentioned that all the features of the embodiment described would function equally with a petrol can of the 'honeycomb' type.

In particular with the embodiment described, it will be noted that as shown in Figure 1, there is provided a totally sealed enclosure in that sealing at the push-button has been specifically addressed as has sealing at the spout connection. Finally tight sealing is also provided at the inlet by virtue of the engagement of the cap 31.

The embodiment shown in Figure 14 is very similar to that described in relation to Figures 1 to 13, and really only differs in relation to the nature of the spout. With this embodiment the spout is of the collapsible or crumple type being manufactured from a special plastics material. Accordingly when the spout is not in use, i.e. when dispensing of liquid from the container is not required, the part of the spout which crumples/collapses is received in the container. However it will be noted that with this spout 101 for the can 100, the spout again has a socket portion 102 which screws down to and locks onto a corresponding integrally formed as part of the can body in the same way as for the boss 20 and socket portion 41 of the previous embodiment. Thus again the spout is permanently attached to the can body after the manufacturing assembly has been completed. Similar parts of the can construction are identified by the same numerals in Figure 14 as for those used in relation to the first embodiment, but with the prefix 100. Figure 14 shows that with the spout 101 in its collapsed state, a cap 103 attached to the body by a strap 104, is screwed onto the socket portion 41 by means of an external screw-thread on said socket portion and an internal screw-thread in the cap. Alternatively the spout 101 could be connected to the body in some other form and the cap could screw directly onto the boss formed as an integral part of the can body. Figure 16 shows that the outer end of the spout 101 is formed, by means of a series of cut-outs, as a plurality of teeth 105,

and Figure 17 shows that the cap 103 is formed with a central interior shaped head 106 which can be pushed into the end of the cap 103 so as to engage the semi-hemispherical end of the head behind the teeth, so that when the cap is pulled outwardly from its Figure 14 position, the head will engage behind the teeth and pull the spout outwardly from its crumpled/collapsed position to its fully extended position shown in Figure 15. After use, the cap can be used to push the spout back into the can, or alternatively this can be accomplished manually. The shaping at the end of the head 106 thereby facilitates the extending of the spout, given that this can sometimes be troublesome with cans in which this use of a crumple spout is known.






FIG. 2





FIG. 3 12








FIG. 5




FIG. 7











FIG. 6





132 131



118 100




FIG. 14

103



FIG. 17

105



FIG. 16

101

102




FIG. 15

THE PATENT OFFICE

10 SEP 2003

Received in Patents  
International Unit

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☒ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER: \_\_\_\_\_**

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**